



**MOTOCOMPRESORES
L'UNITE HERMETIQUE**

Baja Temperatura

R404A

Aceite Polyolester

HP (Potencia)	MODELO	Cilindrada cm ³	Carga Aceite cm ³	Enfriamiento	Consumo en Watts	Rendimiento Frigorífico (Kcal/h)						Volts / No f / Hz	Ø Succión	Ø Descarga	Peso Bruto Kg	H Altura
						Temperatura Evaporación										
						-35°C	-30°C	-23°C	-20°C	-15°C	-10°C					
1/2	FDCO2428M	15,2	887	V	520	220	335	546	670	880	1114	220/1/50	1/2"	1/4"	21,6	271
3/4	FDCO2432M	18,3	887	V	580	282	437	677	813	1052	1340	220/1/50	1/2"	5/16"	22	271
1	FDCO2446M	26,2	887	V	920	497	702	1040	1236	1969	1997	220/1/50	1/2"	5/16"	23,2	282
1 1/2	FDCO2464M	34,5	887	V	1210	637	932	1383	1635	2070	2575	220/1/50	5/8"	3/8"	25	321
1 1/2	FDCO2464T	34,5	887	V	1200	637	932	1383	1635	2070	2575	380/3/50	5/8"	3/8"	25	321
2	FDCO2480M	53,2	1625	V	1740	635	1134	1877	2289	2989	3800	220/1/50	5/8"	1/2"	34,2	370
2	FDCO2480T	53,2	1625	V	1600	635	1134	1877	2289	2989	3800	380/3/50	5/8"	1/2"	34,2	370
2	FDCO2480P	53,2	1625	V	1600	635	1134	1877	2289	2989	3800	380/3/50	5/8"	1/2"	35	370
2 1/2	FDCO2511T	74,3	1625	V	2100	1187	1734	2696	3265	4241	5350	380/3/50	5/8"	1/2"	34,2	370
2,5	FDCO2511P	74,3	1625	V	2100	1187	1734	2696	3265	4241	5350	380/3/50	5/8"	1/2"	35	370
4	FDCO2516T	112,5	1960	V	3000	1499	2325	3745	4587	6055	7771	380/3/50	7/8"	5/8"	44	455
4	FDCO2516P	112,5	1960	V	3000	1499	2325	3745	4587	6055	7771	380/3/50	7/8"	5/8"	45	455
5	FDCO2522T	134,8	1960	V	3700	2044	3045	4758	5750	7490	9511	380/3/50	1"1/8	5/8"	47	455
5	FDCO2522P	134,8	1960	V	3700	2044	3045	4758	5750	7490	9511	380/3/50	1"1/8	5/8"	48	455

Temperatura Condensación: 54°C

V: Ventilación Forzada

